according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : VALDOR FLEX

Product code : Article/SKU: 85334034 UVP: 05991179 Specification:

102000013898

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Herbicide, Plant protection agent

stance/Mixture

Recommended restrictions : Not

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : 2022 Environmental Science FR S.A.S.

For GB - Milton Hall, Ely Rd, Milton, Cambridge CB24 6WZ, United Kingdom

For NI - 3 Place Giovanni Da Verrazzano 69009 Lyon, France

Telephone : 00800 1214 9451

E-mail address of person responsible for the SDS

: service.clients.es.france@envu.com

1.4 Emergency telephone number

For Emergency or Spill call:

+44 20 3807 3798 (24/7 multilingual support)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Short-term (acute) aquatic hazard, Cate-

gory 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Cat-

egory 1

H410: Very toxic to aquatic life with long lasting

effects.

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

!>

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P264 Wash skin thoroughly after handling.P273 Avoid release to the environment.P280 Wear eye protection/ face protection.

Response:

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Additional Labelling

EUH208 Contains Disodium maleate. May produce an allergic reaction.

EUH401 To avoid risks to human health and the environment, comply with the instruc-

tions for use.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Chemical nature : Water dispersible granules (WG)

Components

Chemical name	CAS-No. EC-No. Index-No.	Classification	Concentration (% w/w)
	Registration number		
Diflufenican	83164-33-4	Aquatic Acute 1; H400	35.9967
	616-032-00-9	Aquatic Chronic 1; H410	
		M-Factor (Acute aquatic toxicity): 10,000 M-Factor (Chronic	
		aquatic toxicity): 1,000	
		Acute toxicity esti- mate	
		Acute oral toxicity: > 2,000 mg/kg	
Alkylnaphthalenesulfonic acid, polymer with formaldehyde, sodium salt	68425-94-5	Eye Irrit. 2; H319 Aquatic Chronic 3; H412	9
Aromatic hydrocarbons, C10-13,	1258274-08-6	Skin Irrit. 2; H315	3.6
reaction products with branched nonene, sulfonated, sodium salts	01-2119980591-31	Eye Dam. 1; H318 Aquatic Chronic 3; H412	
lodosulfuron-methyl-sodium	144550-36-7	Aquatic Acute 1; H400	1.0391
	616-108-00-1	Aquatic Chronic 1; H410	
		M-Factor (Acute aquatic toxicity):	
		1,000 M-Factor (Chronic aquatic toxicity): 1,000	
Disodium maleate	371-47-1 206-738-1	Skin Sens. 1B; H317	0.2

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

There is no specific antidote available.

In case of ingestion gastric lavage should be considered in cases of significant ingestions only within the first 2 hours. However, the application of activated charcoal and sodium

sulphate is always advisable.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Silicon oxides Metal oxides Carbon oxides

Fluorine compounds Nitrogen oxides (NOx)

Sulphur oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not swallow.

Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

Dust explosion class : St1

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : Refer to the label and/or leaflet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

•				
Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Kaolin	1332-58-7	TWA (Respirable	2 mg/m3	GB EH40
		dust)		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Aromatic hydrocar-	Workers	Inhalation	Long-term systemic	21.16 mg/m3

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

bons, C10-13, reaction products with branched nonene, sulfonated, sodium salts			effects	
	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Workers	Inhalation	Acute local effects	10 mg/m3
	Workers	Skin contact	Long-term systemic effects	3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	7.46 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2.143 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2.143 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Aromatic hydrocarbons, C10-13,	Fresh water	0.138 mg/l
reaction products with branched		
nonene, sulfonated, sodium salts		
	Freshwater - intermittent	0.357 mg/l
	Marine water	0.0138 mg/l
	Sewage treatment plant	22 mg/l
	Fresh water sediment	44.1 mg/kg dry
		weight (d.w.)
	Marine sediment	4.41 mg/kg dry
		weight (d.w.)
	Soil	8.75 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety goggles

Equipment should conform to EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : > 0.4 mm

Directive : Equipment should conform to EN 374

Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications,

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to EN 143

Filter type : Particulates type (P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : granules

Colour : beige

Odour : characteristic, very faint

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : > 380 °C

Decomposition energy (mass): 40 kJ/kg

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

pH : 8.5 - 10.5 (23 °C)

Concentration: 1 %

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : dispersible

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : Not applicable

Relative density : No data available

Bulk density : 583 - 734 kg/m³

Relative vapour density : Not applicable

Particle characteristics

Particle size : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Flammable solids

Burning number : 2

Self-ignition : 313.00 °C

Method: Tested according to Directive 92/69/EEC.

Dust deflagration index (Kst) : 78 m.b_/s

Dust explosion class : St1

Evaporation rate : Not applicable

Minimum ignition energy : > 1,000.00 mJ

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Skin contact

exposure Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Components:

Diflufenican:

Acute oral toxicity : Acute toxicity estimate (Rat): > 2,000 mg/kg

Method: Expert judgement

Alkylnaphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Acute oral toxicity : LD50 (Rat): > 4,500 mg/kg

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, so-

dium salts:

Acute oral toxicity : LD50 (Rat, male): 4,470 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Iodosulfuron-methyl-sodium:

Acute oral toxicity : LD50 (Rat): 2,678 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.81 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Disodium maleate:

Acute oral toxicity : LD50 (Rat): 3,380 mg/kg

Acute dermal toxicity : LD50 (Rabbit, female): > 2,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Species : Rabbit

Result : No skin irritation

Components:

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, so-dium salts:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Components:

Alkylnaphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Result : Irritation to eyes, reversing within 21 days

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, so-

dium salts:

Species : Rabbit

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Product:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Components:

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, sodium salts:

Test Type : Buehler Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

lodosulfuron-methyl-sodium:

Test Type : Magnusson-Kligman-Test

Exposure routes : Skin contact

Species : Rabbit

Method : OECD Test Guideline 406

Result : negative

Disodium maleate:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : positive

Remarks : Based on data from similar materials

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, sodium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: in vitro micronucleus test Method: OECD Test Guideline 487

Result: negative

Iodosulfuron-methyl-sodium:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Disodium maleate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Diflufenican:

Species : Rat
Application Route : Ingestion
Exposure time : 104 weeks

Method : OECD Test Guideline 453

Result : negative

Iodosulfuron-methyl-sodium:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Disodium maleate:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Diflufenican:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 414

Result: negative

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, sodium salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

lodosulfuron-methyl-sodium:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: negative

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Disodium maleate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Test Type: Embryo-foetal development

Effects on foetal develop-

ment Species: Rat

A " " T

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

lodosulfuron-methyl-sodium:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Diflufenican:

Species : Mouse, male
NOAEL : 62.2 mg/kg
LOAEL : 321.7 mg/kg
Application Route : Ingestion
Exposure time : 105 Weeks

Method : OECD Test Guideline 453

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, so-

dium salts:

Species : Rat

NOAEL : 300 mg/kg

LOAEL : 1,000 mg/kg

Application Route : Ingestion

Exposure time : 29 - 47 Days

Method : OECD Test Guideline 422

Iodosulfuron-methyl-sodium:

Species : Dog
NOAEL : 7 mg/kg
LOAEL : 42 mg/kg
Application Route : Ingestion
Exposure time : 1 yr

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Disodium maleate:

Species : Rat

LOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 2 yr

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

_ _ _ _

ErC50 (Desmodesmus subspicatus (green algae)): 0.0086

mg/l

Exposure time: 72 h

Components:

Diflufenican:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 0.0985 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 0.240 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 : 0.000071 mg/l Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

EC10 : 0.000029 mg/l Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

10,000

Toxicity to fish (Chronic tox-

icity)

EC10: 0.00543 mg/l Exposure time: 28 d

Species: Pimephales promelas (fathead minnow)

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chron-

NOEC: 0.0124 mg/l Exposure time: 28 d

ic toxicity)

Species: Chironomus riparius (harlequin fly)

M-Factor (Chronic aquatic

toxicity)

1,000

Alkylnaphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10 - 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10: > 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, sodium salts:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 35.7 mg/l

Exposure time: 96 h

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Raphidocelis subcapitata (freshwater green alga)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (activated sludge): 222 mg/l Toxicity to microorganisms

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

EC10: 6.9 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

lodosulfuron-methyl-sodium:

LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Lemna gibba (gibbous duckweed)): 0.81 μg/l

Exposure time: 14 d

M-Factor (Acute aquatic tox-

icity)

1,000

Toxicity to microorganisms EC50 (activated sludge): 874 mg/l

Exposure time: 3 h

Toxicity to fish (Chronic tox-

icity)

NOEC: 7.79 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10: 7.9 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic

toxicity)

1,000

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Disodium maleate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Test substance: Neutralised product Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 10 -

100 ma/l

Exposure time: 72 h

Test substance: Neutralised product Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Test substance: Neutralised product Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1 mg/l

Exposure time: 18 h

Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Diflufenican:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 9 - 21 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Alkylnaphthalenesulfonic acid, polymer with formaldehyde, sodium salt:

Biodegradability : Result: Not readily biodegradable.

Remarks: Based on data from similar materials

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, sodium salts:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 29 % Exposure time: 28 d

Method: OECD Test Guideline 301D

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

01.04.2023 1.0 11188570-00001 Date of first issue: 01.04.2023

Disodium maleate:

Biodegradability Result: Readily biodegradable.

Method: OECD Test Guideline 301B

Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Diflufenican:

Bioaccumulation Species: Oncorhynchus mykiss (rainbow trout)

> Bioconcentration factor (BCF): 1,650 Method: OECD Test Guideline 305

Partition coefficient: n-

log Pow: 4.2

Method: OECD Test Guideline 117 octanol/water

Aromatic hydrocarbons, C10-13, reaction products with branched nonene, sulfonated, so-

dium salts:

Partition coefficient: nlog Pow: -3.3

octanol/water Remarks: Calculation

lodosulfuron-methyl-sodium:

Partition coefficient: n-

octanol/water

log Pow: -0.7

Disodium maleate:

Partition coefficient: nlog Pow: -0.516 octanol/water Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : It is best to use all of the product in accordance with label

directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local

guidelines.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Follow advice on product label and/or leaflet.

Empty containers retain residue and can be dangerous.

Do not re-use empty containers.

Waste Code : The following Waste Codes are only suggestions:

used product

02 01 08, agrochemical waste containing hazardous sub-

stances

unused product

02 01 08, agrochemical waste containing hazardous sub-

stances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3077
ADR : UN 3077
RID : UN 3077
IMDG : UN 3077
IATA : UN 3077

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Diflufenican, Iodosulfuron-methyl-sodium)

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

N.O.S.

(Diflufenican, lodosulfuron-methyl-sodium)

RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Diflufenican, lodosulfuron-methyl-sodium)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Diflufenican, lodosulfuron-methyl-sodium)

IATA : Environmentally hazardous substance, solid, n.o.s.

(Diflufenican, lodosulfuron-methyl-sodium)

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 9

 ADR
 : 9

 RID
 : 9

 IMDG
 : 9

 IATA
 : 9

14.4 Packing group

ADN

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) : Y956
Packing group : III

Labels : Miscellaneous

22 / 25

956

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

IATA (Passenger)

Packing instruction (passen- : 956

ger aircraft)

Packing instruction (LQ) : Y956
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Active substance : 36 %

Diflufenican

1 %

lodosulfuron-methyl-sodium

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2

E1 ENVIRONMENTAL 100 t 200 t

HAZARDS

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

: Not applicable

lines.

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regula-

according to Regulation (EC) No. 1907/2006 as amended by UK REACH Regulations SI 2019/758



VALDOR FLEX

Version Revision Date: SDS Number: Date of last issue: -

1.0 01.04.2023 11188570-00001 Date of first issue: 01.04.2023

tion (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Eye Irrit. 2 H319 Based on product data or assessment
Aquatic Acute 1 H400 Based on product data or assessment

Aquatic Chronic 1 H410 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

XI / EN